

TECHNICAL SPECIFICATIONS

Antennas mounting

It is imperative to maximize the isolation between the antennas.

External antennas must be installed at a **minimal distance of 50 cm from one another.**

If only one external antenna is installed, it must be installed at a **minimal distance of 50 cm from the control panel.**

868 MHz external RF antenna

Parameters	Min	Typical	Max	Unit	Comments
Frequency Band	868		870	MHz	<i>Mono Band</i>
Impedance	50			Ω	
Return loss	10			dB	<i>VSWR < 1.9 : 1</i>
Polarization	vertical				
Radiation pattern	omni-directional				<i>In horizontal plan</i>
Gain			3	dBi	<i>ETSI agreement limit</i>
Operating temperature	-45		85	°C	

Example : GP868 (http://www.aurelwireless.com/wp-content/uploads/shortform/650200313G_sf.pdf)

Note : The RF antenna has to be enabled in the control panel parameters.

External 2G-3G antenna

Paramètres	Min	Typical	Max	Unit	Comments
Frequency bands	824		960	MHz	<i>GSM 850, E-GSM 900...</i>
	1710		2170		<i>DCS 1800, PCS1900, UMTS...</i>
Impedance	50			Ω	
Return loss	6			dB	<i>VSWR < 3 : 1</i>
Radiation pattern	omni-directional				<i>In horizontal plan</i>
Operating temperature	-45		85	°C	



868 MHz external RF antenna



External 2G-3G antenna

EMEA SALES

23, avenue du Général Leclerc
 92340 BOURG-LA-REINE
 FRANCE
 E-Mail : emeasales@rsivideotech.com

North American Headquarters

1375 Willow Lake Blvd, Suite 103
 Vadnais Heights, MN 55110
 USA
 E-Mail : usasales@rsivideotech.com

